

Arctic Fire

gültig ab / valid from

10.02.2025

0,21 W/m²K

U-Wert
U-value

0,14 W/m²K

U-Wert mit ISO-Oberdeckel
U-value with ISO upper lid

	A	A	B	C	D	E
	Lukenkasten frame size	Rohbaumaß rough opening size	lichte Raumhöhe floor to ceiling height	Ausklappraum fold-out space	Grundmaß basic size	Schwenkraum Oberdeckel automatisch swivel range top cover automatic
Version	L x B x H in mm	L x B in mm	in mm	in mm	in mm	in mm
110 / 70	1090 x 690 x 455	1100 x 700	max. 2650	650	1200	1510
120 / 60	1190 x 590 x 455	1200 x 600	max. 2750	580	1200	1610
120 / 70	1190 x 690 x 455	1200 x 700	max. 2750	580	1200	1610
130 / 70	1290 x 690 x 455	1300 x 700	max. 2750	480	1200	1420
140 / 70	1390 x 690 x 455	1400 x 700	max. 2750	380	1200	1515
140 / 70	1390 x 690 x 455	1400 x 700	max. 3000*	400	1200	1515

*bei Raumhöhe 300 cm ist keine Treppenverlängerung möglich / no staircase extension possible for this height

EI₃₀

Brandhemmende Wirkung
fire-retardant effect
