

Type 13 X-Large

gültig ab / valid from
10.02.2025

1,3 W/m²K

u-Wert
u-value

	A	A	B	C	D	E
	Lukenkasten frame size	Rohbaumaß rough opening size	lichte Raumhöhe floor to ceiling height	Ausklappraum fold-out space	Grundmaß basic size	Schwenkraum Oberdeckel zur Seite swivel range top cover to the side
Version	L x B x H in mm	L x B in mm	in mm	in mm	in mm	in mm
140 / 92	1390 x 910	1400 x 920	2150 – 2290	0	1540	1400
140 / 92	1390 x 910	1400 x 920	2300 – 2450	100	1600	1400
140 / 92	1390 x 910	1400 x 920	2400 – 2500	150	1700	1400
140 / 92	1390 x 910	1400 x 920	2500 – 2680	200	1780	1400
140 / 92	1390 x 910	1400 x 920	2610 – 2750	250	1820	1400
140 / 92	1390 x 910	1400 x 920	2750 – 2900	300	1900	1400
140 / 92	1390 x 910	1400 x 920	2850 – 2950	400	1950	1400
140 / 92	1390 x 910	1400 x 920	2950 – 3170	600	2050	1400
140 / 92	1390 x 910	1400 x 920	3180 – 3400	800	2140	1400

EL₂30

Brandhemmende Wirkung
fire-retardant effect

